

Specifications



The DocuTech 6100/6115/6135 deliver high-value digital services like print on demand, distribute then print, and 1:1 marketing. Now, you can start on the road to digital printing success at a pace that's just right—up to 135 pages per minute.

DocuTech 6100/6115/6135 are ideal entry points to enter the digital world, or an economical way to complement your current DocuTech system capacity. In either case, your business will move faster and more productively when it is... **powered by DocuTech.**

Xerox DocuTech 6100/6115/6135





The PowerPlus Series extends DocuTech's industry-leading capabilities with enhancements that expand the media latitude and complex job capabilities of the system such as a 3 Tray Interposer and support for large format and coated stocks.

For more information on the Xerox DocuTech® 6100/6115/6135 Production Publishers and the PowerPlus Series, call **1-800 ASK XEROX** or visit us on the Web at: www.xerox.com

Xerox DocuTech 6100/6115/6135 Production Publisher and the PowerPlus Series Specifications

Printer Control Module

- Sun Blade™ 2500
- 1.28 GHz UltraSparc III processor
- 36 GB system disk
- 2 GB memory
- DVD-ROM Drive
- 17.0" color flat panel display
- Keyboard and mouse
- Ethernet interface (10/100BaseT)
- Controller stand (optional)

Printer Module

- Xerographic Engine
- Print speeds:
 - DocuTech 6100: Up to 96 ppm (8.5" x 11"/A4)
 - DocuTech 6115: Up to 115 ppm (8.5" x 11"/A4)
 - DocuTech 6135: Up to 135 ppm (8.5" x 11"/A4)
- On-site upgrades are available for the DocuTech 6100 and 6115*
- Simplex or duplex printing
- Enhanced 600 x 600 dpi laser raster output
- ImageSense Technology with redesigned 85+ and 106+ line screens and new 121 and 140 line screens
- On-line, right and left side stitching/binding
- Optional Interposers:
 - 2 Tray Interposer *or*
 - 3 Tray Interposer

Throughput Materials

(Printing and finishing)

- Stock weights: 16 lb. bond to 110 lb. index (60 g/m² to 200 g/m²)
- Sizes: 8" x 10" to 14.33" x 17" (203 mm x 254 mm to 363 mm x 432 mm)
- Narrow format option available for 7" width
- Extra large format option available for up to 14.33" x 19.2**
- Lightweight paper option available for 13 lb. bond*

PowerPlus Series Options**

- 3 Tray Interposer
- PowerPlus Large format option available for up to 14.33" x 18.5" (364 mm x 470 mm)
 - Tray 3 14.0" x 18.0" (356mm x 457mm)
 - Tray 4,5,(6) up to 14.33" x 18.5" (364 mm x 470 mm)

Paper Input Capacity

(Sheet capacity all at 20 lb./75 g/m²)

- Tray 1 1,100 sheets; 8" x 10" to 9" x 14.33" (203 mm x 254 mm to 229 mm x 364 mm)
- Tray 2 600 sheets; 8" x 10" to 9" x 14.33" (203 mm x 254 mm to 229 mm x 364 mm)
- Tray 3 2,600 sheets of up to 14.33" x 17" (364 mm x 432 mm)

Paper Input Option - Interposers

- 2 Tray Interposer (for a total of 5 input paper trays with auto tray switching and document inserts):
 - Tray 4*** 550 sheets of up to 14.33" x 17" (364 mm x 432 mm)
 - Tray 5 2,600 sheets of up to 14.33" x 17" (364 mm x 432 mm)
- 3 Tray Interposer (for a total of 6 input paper trays with auto tray switching and document inserts):
 - Tray 4*** 550 sheets of up to 14.33" x 17" (364 mm x 432 mm)
 - Tray 5 550 sheets of up to 14.33" x 17" (364 mm x 432 mm)
 - Tray 6 550 sheets of up to 14.33" x 17" (364 mm x 432 mm)

Paper Output Options

- Stacker: 3,000 sheets at 20 lb. (75 g/m²)
Optional: 5,000 sheets at 20 lb. (75 g/m²) (with one High Capacity Stacker)
Optional: 10,000 sheets at 20 lb. (75 g/m²) (with two High Capacity Stackers)
- Stitcher: 2 - 70 sheets at 20 lb. (75 g/m²)
1 or 2 adjustable stitches
- Binder: 15 - 125 sheets at 20 lb. (75 g/m²)
- Tape colors: Black, blue, red, brown, gray, white or green
- 425 11" binds per tape reel
- SquareFold Booklet Maker (optional)
- Fully automatic booklet making system
- All operator settings are made with the push of a few buttons
- Up to 22 sheets at 20 lb., 26 sheets at 16 lb, or 33 sheets with light weight paper
- Paper sizes:

	Width	Length
Min.	8" (203 mm)	10" (254 mm)
Max.	12.3" (312 mm)	18.2" (462 mm)

- Cover Insertion Module (CIM) (optional)
- Adjustable saddle stitch heads, folder, trimmer
- Supports Level 1 Document Finishing Architecture (DFA)

Client Environments Supported

- Windows 95/98, NT, 2000, XP
- Mac OS 7.6 and above
- Sun OS 4.1.3 / Solaris 1.1.1B
- Solaris 2.3 / 2.4 / 2.5.1 / 2.6 / 8.x

PDLs and Data Formats

- Adobe PostScript Level 3/PDF
- PCL 6 • TIFF • ASCII • Optional LCDS
- FreeFlow™ Variable Information Suite

Native Network Environments

- TCP/IP • AppleTalk • HTTP
- Novell (SPX-IPX) • IPP • SNMP
- Optional Channel Connectivity

Electrical Requirements

- Printer Controller:
 - 100/240 VAC + 10%, 47-63 Hz
- Printer Module:
 - 120/208 or 120/240 VAC, 60 Hz, 50 amp service, NEMA 14-30 R (domestic)
 - 200/240 VAC ± 10%, 50 Hz or 3 phase WYE connection, 380 VAC ± 10%, 50 Hz
 - 380 VAC ± 10%, 50 Hz
 - KVA rating: Standby: 2.73; Operating: 6.45 (without Interposer). Standby: 2.80; Operating: 7.65 (with Interposer)
 - Agency certification: UL 1950 IEC 950, CSA 22.2 - 950, FCC (Class A), EN55022 (Class A), CISPR22 (Class A), EN50082-1: 1992 (Generic Immunity Standard), and ICES003 (Class A)
- Interposer (optional):
 - 100/240 VAC + 10%, 47-63 Hz, 10A

Physical Characteristics

Width	Depth	Height	Weight
Printer Controller - Processor Module			
10" (254 mm)	24" (610 mm)	17.9" (455 mm)	70 lbs. (32 kg)
Printer Controller - Controller Stand			
30" (762 mm)	30" (762 mm)	38" (965 mm)	170 lbs. (76.8 kg)
Printer Controller - 17.0" Flat Panel Display			
18" (475 mm)	9.5" (241 mm)	19.25" (489 mm)	22 lbs. (10 kg)
Printer Module (without optional Interposer)			
133" (3379 mm)	46" (1165 mm)	48.3" (1226 mm)	2502 lbs. (1136 kg)
Interposer (optional)			
45.9" (1165 mm)	32.3" (821 mm)	49.0" (1240 mm)	710 lbs. (322 kg)

Please reference the specification sheets for Xerox FreeFlow™ Makeready, FreeFlow™ Process Manager, and FreeFlow™ Web Services for complete details.

For information on great applications from Xerox Supplies, call **1-800-822-2200 in the USA** or **1-800-668-0199 in Canada**



*Contact your Xerox Sales Representative for more details.

**PowerPlus features available for new printer installations only. Each option sold separately.

***Tray 4 only accepts sheets which do not need to be imaged, i.e., covers and inserts.